

Rejex



Product Description

RejeX protects and beautifies painted metal, glass, acrylic, gel coat, fiberglass, glossy plastic & polished metal surfaces.

RejeX has a higher refractive index than waxes, so it produces richer, deeper looking colours and a lustrous long-lasting finish.

RejeX protects from UV, even in New Zealand and Australia, for up to 9 months.

Rejex treated surfaces are fast and easy to clean.

Application Suggestion

Cars, boats and aircraft. Radar domes, Plexiglass Windows, shower areas, RV kitchens. Bimini and tent-windows (clears).

Rejex will make "milky" and light scratching on clear's and plastic windows almost invisible. Perfect for yachts, cars, RV's wind visors and all Plexiglass/Perspex windows. It also rejuvenates bathroom and galley surfaces in boats and motorhomes, making plastic surfaces shiny again and thus easier to clean.

Direction of use

Ideally, RejeX should be applied to a cool, dry, clean surface. When over 30° C, be sure to apply RejeX out of direct sunlight. If the surface is too hot, the coating can cure before it has properly bonded to the surface, so it may not perform up to its potential.

RejeX is wiped on in a rotary motion. Allow to dry to a haze for approximately 20 minutes, wipe off, then allow to cure for 8-12 hours (depending on the humidity; the higher the humidity, the faster the cure). Curing is required to allow the monomers (polymer building blocks) that make up RejeX to attach to the surface being treated and to cross link into a crystal-clear, impervious film. It is important to allow RejeX to cure for 8-12 hours after the haze has been wiped off. If the coating is exposed to contaminants such as oil, fuel, soot, hard water, tree sap, cleaners, etc. before it has cured, the contaminants may interfere with or embed in the protective film.

The product is not meant to be used on porous surfaces, highly oxidized painted surfaces, or to fill deep scratches. RejeX can be applied in multiple coats, allowing 8 hours curing time between coats for deeper colour and greater depth of gloss. RejeX can be used over existing wax; however, the duration of protection will be reduced as the softer underlying wax degrades comparatively quickly. There is no reason to wax over RejeX. As already stated, RejeX leaves a shinier, longer-lasting finish than wax... and waxes will have difficulty adhering to RejeX!

If a RejeX-treated surface needs repainting, normal paint preparation is all that's required. Abrasive cleaners, polishes, rubbing compounds and some chemical paint strippers can remove RejeX.

Safety brief / precautions

Make sure to stay safe when working at height, i.e. scaffolding around boats or on the roof of your motorhome. DO NOT apply Rejex on plastic floors or shower trays as the coating will be extremely slippery, especially when wet ! Boat tables which had Rejex applied will be very slippery, too !

Keep away from children, do not drink or mix with food.

For full safety briefing please see SDS sheet.