

# BIO SLIDE™

## READY-TO-USE CONCRETE REPELLENT

### PRODUCT HIT POINTS

- Premium quality “architectural grade” formula
- Non-staining; will not stain or discolor
- No unpleasant odor; does not spoil or go rancid
- Superior sprayability for easy, even application
- Will not clog spray tips
- Does not wash off with water
- Helps ensure the highest quality architectural concrete finishes by minimizing voids and bug holes
- The high-performance alternative for concrete ready-mix trucks, pumpers, screeds and other paving equipment to prevent adherence and build-up of concrete

### DESCRIPTION

Bio Slide is a premium, high-purity concrete repellent coating that facilitates easy removal of concrete from roadworking equipment, as well as minimizing voids, bug holes and build-up when using concrete forms. Designed to be applied with a single thin coat, Bio Slide reduces waste and increases productivity.

When used on concrete equipment and behind the ring on concrete ready-mix trucks, Bio Slide facilitates the quick and easy removal of concrete film and buildup. A quick spray of Bio Slide behind the ring on ready-mix trucks can easily cut cleanup time in half. This also greatly reduces the need for acid-based concrete removers and harsh cleaners, which over the long haul saves wear and tear on the equipment – greatly extending equipment lifespan and maintaining resale value.



### SUGGESTED APPLICATIONS

- Architectural grade form release ideal for intricate decorative concrete molds
- ‘Behind-the-ring’ concrete repellent
  - Protective coating for ready-mix trucks and other concrete equipment
  - Paint gun coating (prevents paint adhesion)





## PROPERTIES

<b>Appearance:</b>	Transparent	<b>Autoignition Temperature:</b>	Not established
<b>Physical State:</b>	Non-viscous liquid	<b>Volatile by volume (%):</b>	0
<b>Odor:</b>	Hydrocarbon	<b>Vapor Density (Air=1) :</b>	>1
<b>Color:</b>	Amber	<b>Evaporation Rate (BuAc=1) :</b>	<0.01
<b>Viscosity, cSt @ 40°C:</b>	<20.5	<b>Vapor Pressure, mmHg @23°C:</b>	Not established
<b>cSt @ 100°C:</b>	Not established	<b>Solubility in water:</b>	Insoluble
<b>pH:</b>	Not established	<b>Octanol/Water Partition:</b>	Not established
<b>Boiling Point/ Range:</b>	> 400°F / 200°C	<b>VOC Content g/l (%):</b>	0
<b>Melting Point:</b>	Not established	<b>Specific Gravity @15.6°C:</b>	0.869
<b>Flash Point:</b>	> 93°C / 200°F	<b>Pour Point:</b>	Not established
<b>Method:</b>	Pensky-Martens Closed Cup	<b>Non-volatile by Volume (%):</b>	100
<b>Lower Explosive Limit, vol %:</b>	Not established	<b>Dielectric Strength (KV):</b>	Not applicable
<b>Upper Explosive Limit, vol %:</b>	Not established		

## PRODUCT CODES

Part Number	UPC Code	Product Description
32204	-	1 gallon
32205	-	5 gallon
32208	-	20 gallon
32202	-	30 gallon
32201	-	55 gallon

