BLAST OFF™ Safety Data Sheet

Product Name:	BLAST OFF™
Product Numbers:	22501, 22502, 22504, 22505
Product Type and Use:	Concrete and Rust Remover
Manufacturer:	U.S. Corrosion Technologies, LLC
	2638 National Drive, Garland, TX 75041
Contact:	Telephone: 972-271-7361 Fax: 972-278-9721
Emergency Telephone:	CHEMTREC [®] USA (800) 424-9300
	Outside US +1 (703) 527-3887
	NZ Poison emergency no: 0800 POISON (0800 764 766)
Distributor in New Zealand:	Corrosion Control NZ
	48 Riverside drive
	Whangarei 0112
	Northland
	New Zealand
	Tel: +64 9-438-88-00
	Email: tom@corrosionx.org

2. HAZARDS IDENTIFICATION

Hazard	ard Classification			
	Health Hazard(s)			

1. IDENTIFICATION

nearth nazara(3)	
Skin Irritation	Category 1B
Eye Irritation	Category 1
Acute Toxicity - Inhalation	Category 4
Acute Toxicity - Oral	Category 4
Physical Hazard(s)	
Corrosive to metals	Category 1
Hazard(s) not otherwise class	ified
None	
Labeling	
Signal Word	DANGER

Signal Word: Pictograms: Statements of Hazard

Hazard Statements

Causes severe skin burns and eye damage

Corrosion

Harmful if inhaled or swallowed

May be corrosive to metals

Precautionary Statements

Wear protective gloves, eye and face protection. Do not breathe vapors or mist. Use only outdoors or in a wellventilated area. Take off immediately all contaminated clothing and wash it before reuse. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Store locked up. Keep only in original container. Absorb spillage to prevent material damage. Store in corrosive resistant container with resistant inner liner. Dispose of contents and container in accordance with applicable regulations.

If on skin: Rinse skin with water or shower. Immediately call a poison center or doctor.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor.

If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Percent by Wt.		
Urea Hydrochloride	506-89-8	75-99*		
* Exact percentage of composition has been withheld as a trade secret				

4. FIRST AID MEASURES

General Advice: Causes skin and eye damage. Avoid contact. Do not swallow. Avoid breathing vapors or mist. Use with adequate ventilation. Keep container closed.

Inhalation: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center or doctor. **Skin Contact:** Remove contaminated clothing. Flush skin with plenty of water. Remove contaminated clothing and wash before reuse. Immediately call a poison center or doctor.

Eye Contact: Immediately flush cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.

Ingestion: Do not give anything by mouth to an unconscious person. Do not induce vomiting unless advised to do so by a doctor or poison control center. Rinse mouth. Immediately call a poison center or doctor.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Product does not support combustion. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Suitable: Carbon Dioxide, Dry Chemical, and Foam Unsuitable: Alcohol, Alcohol based solutions

Fire Fighting Procedures: As in any fire, wear self-contained breathing apparatus, pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Cool fire-exposed containers with water spray.

Unusual Fire and Explosion Hazards: Flammable hydrogen gas may be produced on contact with aluminum, tin, lead and zinc Hazardous Combustion/ Decomposition Products: Thermal decomposition can lead to release of toxic and irritating hydrogen chloride. Oxides of carbon and nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions / Protective Equipment / Emergency Procedures: Use caution as spills may be slippery. Ensure adequate ventilation. Use personal protective equipment.

Methods and materials for containment and cleaning up: Dike and contain large spills with inert absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer liquid to plastic containers. Flush surfaces with plenty of water to sanitary sewer system (If permitted by local sewer regulations). Do not store or dispense into metal containers; especially aluminum. Use clean non-sparking tools to collect absorbed material and transfer to a properly labeled container for recovery or disposal according to applicable regulations.

7. HANDLING AND STORAGE

HANDLING

Precautions for Safe Handling: Avoid skin and eye contact. Use with adequate ventilation. Avoid breathing mist or vapors. Follow all SDS/label precautions.

STORAGE

Conditions to avoid: Store in a cool, dry, well-ventilated place in the original container. Do not transfer or store in metal containers. Keep container tightly closed when not in use. Avoid excess heating and high temperatures.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

	ACGIH	09	SHA	NIOSH			
Component	TLV	TLV	PEL	PEL	IDLH	STEL	
	ppm	mg/m3	ppm	mg/m3	ppm	mg/m3	
Hydrochloric Acid	2	Not Est.	5	7	50	Not Est.	
Engineering Controls	Lise with local exhaust ventilation	Ensure adem	iate ventilat	ion especially	in confined	areas	

Engineering Controls: Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas. Personal Protection

Respiratory Protection: None required under normal use conditions. In case of insufficient ventilation, wear a suitable NIOSH approved air purifying respirator with acid vapor cartridge.

Hand / Skin Protection: Wear impermeable gloves such as neoprene or nitrile rubber gloves. Gauntlets and apron may be worn depending on the extent of exposure.

Eye / Face Protection: Face shield with safety glasses with side-shields.

General Hygiene Measures: Avoid contact. Always wash hands and face before eating, drinking or smoking. Remove and wash contaminated clothing before re-use. An eyewash station and washing facilities should be readily accessible to the area of use. See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Transparent	Autoignition Temperature:	Not established
Physical State:	Non-viscous liquid	Volatile by volume (%):	1-25
Odor:	None	Vapor Density (Air=1):	1
Color:	Light Yellow	Evaporation Rate (BuAc= 1):	<1
Viscosity, cSt @ 40°C:	Not established	Vapor Pressure, mmHg @23°C:	21.1
cSt @ 100°C:	Not established	Solubility in water:	Complete
pH:	<1	Octanol/Water Partition:	Not established
Boiling Point/ Range:	>200°F / 93°C	VOC Content g/l (%):	0 (0)
Melting Point:	Not established	Specific Gravity @15.6°C:	1.09
Flash Point:	Not applicable	Pour Point:	Not established
Method:	Not applicable	Non-volatile by Volume (%):	75-99
Lower Explosive Limit, vol %:	Hydrogen, 4	Dielectric Strength:	Not applicable
Upper Explosive Limit, vol %:	Hydrogen, 75	5	11

10. STABILITY AND REACTIVITY

Stability: Stable at ambient temperatures and up to 230°F/110°C.

Conditions to Avoid: Heating above 230°F/110°C results in an exothermic decomposition with rapid release of carbon dioxide gas. **Hazardous Polymerization:** Will not occur.

Materials to Avoid: Strong bases/alkali, strong oxidizing agents, reducing agents, magnesium, aluminum and other reactive metals, rubber, leather, chlorate, nitrates, sulfides, sulfites and hypochlorites (chlorine bleach).

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information: Not established

Ingredient Information: Urea Hydrochloride Orl-rat LD50 - 1121 mg/kg

Hydrochloric acid Orl-Rat LD50 700 mg/kg, Skn-Rbt LD50 > 5010 mg/kg, Ihl-Rat LC50 3124 ppm 1 h Acute Effects

Signs and Symptoms of Overexposure: Skin and serious eye irritation, Coughing, Sneezing

Inhalation: Mist and vapors may cause respiratory irritation with nasal discomfort and discharge, coughing and sneezing. **Skin Contact:** May cause redness, pain and burns.

Eye Contact: May cause tearing, redness, pain, and swelling of the conjunctiva. May cause blindness.

Ingestion: May cause pain, nausea, vomiting and diarrhea. Aspiration of product into the lungs may occur during ingestion or vomiting, resulting in lung injury.

Primary Route(s) of Exposure: Eyes, Skin, Inhalation

Primary Route(s) of Entry: Inhalation, Ingestion

Medical Conditions Aggravated by Exposure: May aggravate existing skin, eye and respiratory conditions including asthma and dermatitis.

12. ECOLOGICAL INFORMATION

Product Data: Not established

Ingredient Data: Urea Hydrochloride 96 hour LC50 >140 mg/L (rainbow trout), 48 hour LC50 71.1 mg/L (ceriodaphnia dubia), 15 minute IC50, 16.23% effect at a concentration of 10 mg/L (Vibrio fischeri, 4H6002), EC50 70-100 mg/kg (daphnia)

Elimination Information

Persistence and degradability: Not biodegradable. Hydrochloric acid will be neutralized to chloride by alkalinity present in natural environment.

Mobility in soil: Hydrochloric acid will be neutralized by naturally occurring alkalinity. The acid will permeate soil, dissolving some soil material and will then neutralize.

13. DISPOSAL CONSIDERATIONS

Product: Dispose of in accordance with applicable regulations. **Container:** Empty remaining contents. Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORT INFORMATION

Road Transport

Proper Shipping Name: Corrosive Liquid, Acidic, Organic, N.O.S. (Urea Hydrochloride) UN number: UN3265 Class: 8 Packing Group: PG II

Air Transport

Proper Shipping Name: Corrosive Liquid, Acidic, Organic, N.O.S. (Urea Hydrochloride) UN number: UN3265 Class: 8 Packing Group: PG II

Ocean Transport

Proper Shipping Name: Corrosive Liquid, Acidic, Organic, N.O.S. (Urea Hydrochloride) UN number: UN3265 Class: 8 Packing Group: PG II

15. REGULATORY INFORMATION

U.S. Federal Regulations

Toxic Substances Control Act (TSCA): All components are included on the Inventory Superfund Amendments and Reauthorization Act (SARA) Title III:

Immediate	Delayed	Fire	Pressure	Reactivity
Hazard	Hazard	Hazard	Hazard	Hazard
Х	-	-	-	

New Zealand HSNO classification

8.2B, 8.3A, 6.1D, 8.1A

16. OTHER INFORMATION

Prepared by: U.S. Corrosion Technologies, LLC Technical Services Department Revision Date: 6/22/2015 Revision Indicator: v 2.0

National Fire Protection Association (704)Health: 3Flammability: 0Reactivity: 0Other: -

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damage incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical and application of such products is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the sole responsibility of the user to comply with all applicable Federal, State and Local Laws and Regulations. Any questions with regards to information contained herein should be referred to: U. S. Corrosion Technologies, LLC (972) 271-7361.