

1. IDENTIFICATION

Product Name: ReelX™
Product Numbers: 77000
Revision Date: 11 June 2020
Version Number: NZ1.1
Previous revision date: 10 June 2019
Relevant identified uses of the substance or mixture and uses advised against
Identified Uses: Corrosion Inhibitor / Moisture Displacer / Lubricant
Uses advised against: Other uses are not recommended unless an assessment is completed, prior to commencement of that use, which demonstrates that the use will be controlled.

Details of the supplier of the safety data sheet

Manufacturer: Corrosion Technologies
2638 National Drive, Garland, TX 75041
Telephone: 972-271-7361
Fax: 972-278-9721
Email: info@corrosionx.com
Website: www.corrosionx.com
Distributor in New Zealand: Corrosion Control NZ
48 Riverside drive
Whangarei 0112
Northland
New Zealand
Tel: +64 9-438-88-00
Email: tom@corrosionx.org

Emergency Telephone Number

Poisons Information Centre

NZ Poison emergency no: 0800 POISON (0800 764 766)

For Chemical Emergency ONLY (spill, leak, fire, exposure or accident), 24-hour emergency telephone, call CHEMTREC® New Zealand (Auckland) +(64)-98010034.

2. HAZARDS IDENTIFICATION

Hazard Classification

Health Hazard(s)

Eye Irritation Category 2B
Acute toxicity – Oral Category 5

Physical Hazard(s)

None

Hazard(s) not otherwise classified

None

Labeling

Signal Word:

DANGER

Pictograms:

Exclamation Mark



Statements of Hazard

Hazard Statements

Causes eye irritation
May be harmful if swallowed

Precautionary Statements

Wash thoroughly after handling. Store locked up. Dispose of contents and container in accordance with applicable regulations.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a doctor or poison center.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS Number	Percent by Wt.
Mineral oil	8042-47-5	10-15*
Hydrotreated neutral base oil	72623-85-9	65-75*

* Exact percentage of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General Advice: Causes eye irritation. Avoid eye contact. Aspiration hazard; do not swallow. May cause lung damage. Use with adequate ventilation. Avoid breathing mist. Keep container closed.

Inhalation: Remove from exposure area to fresh air. Give artificial respiration if not breathing. Get medical attention.

Skin Contact: Wipe excess from skin; remove contaminated clothing. Wash with soap and water.

Eye Contact: Flush eyes with plenty of water for 15 minutes while holding eyelids open. Seek medical attention if irritation persists.

Ingestion: Rinse mouth. Do NOT induce vomiting. Immediately call a physician or poison control center.

5. FIRE FIGHTING MEASURES

Extinguishing Media: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Suitable: Carbon Dioxide, Dry Chemical, and Foam

Unsuitable: Alcohol, Alcohol based solutions, any other media not listed above.

Fire Fighting Procedures: As in any fire, wear self-contained breathing apparatus, pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Unusual Fire and Explosion Hazards: None known.

Hazardous Combustion/ Decomposition Products: Oxides of carbon, sulfur, calcium, magnesium and phosphorous.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions / Protective Equipment / Emergency Procedures: Use caution as spills may be slippery. Ensure adequate ventilation. Use personal protective equipment.

Methods and materials for containment and cleaning up: Do not flush into surface water or sanitary sewer system. Dike and contain spillage. Soak up with absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite). Use clean tools to collect absorbed material and transfer to a properly labeled container for disposal according to applicable regulations.

7. HANDLING AND STORAGE

HANDLING

Precautions for Safe Handling: Avoid eye contact. Use with adequate ventilation. Avoid breathing mist. Follow all SDS/label precautions even after container is empty due to residue.

STORAGE

Conditions to avoid: Store in a cool, dry, well-ventilated place in the original container. Keep container closed when not in use. Avoid excess heating and high temperatures.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

EXPOSURE LIMITS

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Component	ACGIH		OSHA			
	TLV ppm	TLV mg/m ³	PEL ppm	PEL mg/m ³	STEL ppm	STEL mg/m ³
Mineral Oil	Not Est.	5	10	5	Not Est.	2500
Hydrotreated neutral base oil	Not Est.	5	10	5	Not Est.	2500

Engineering Controls: Use with local exhaust ventilation. Ensure adequate ventilation, especially in confined areas.

Personal Protection

Respiratory Protection: None required under normal use conditions. In case of insufficient ventilation and for exposures above occupational exposure limits wear a NIOSH approved air purifying respirator with organic vapor cartridge.

Hand / Skin Protection: None typically required. For sensitive skin; wear impermeable gloves such as neoprene or nitrile rubber gloves. Gauntlets and apron may be worn depending on the extent and duration of exposure.

Eye / Face Protection: Safety glasses with side-shields. An eyewash station should be available to the area of use.

General Hygiene Measures: Avoid eye contact. Always wash hands and face before eating, drinking or smoking. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Transparent	Autoignition Temperature:	Not established
Physical State:	Non-viscous liquid	Volatile by volume (%):	4
Odor:	Fresh scent	Vapor Density (Air=1) :	5.9
Color:	Greenish-brown	Evaporation Rate (BuAc=1) :	<1
Viscosity, cSt @ 40°C:	33.2	Vapor Pressure, mmHg @20°C:	<0.05
cSt @ 100°C:	7.0	Solubility in water:	Insoluble
pH:	Not applicable	Octanol/Water Partition:	Not established
Boiling Point/ Range:	>421°F / 216°C	VOC Content g/l (%):	0 (0)
Melting Point:	Not established	Specific Gravity @15.6°C:	0.895
Flash Point:	143°C / 290°F	Pour Point:	-22°F / -30°C
Method:	Cleveland Open Cup	Non-volatile by Volume (%):	96
Lower Explosive Limit, vol %:	4.8	Dielectric Strength (KV):	37
Upper Explosive Limit, vol %:	7		

10. STABILITY AND REACTIVITY

Stability: Stable at ambient temperatures.

Conditions to Avoid: Excess heating above 356°F / 180°C over long periods of time degrades the resin. Avoid high temperatures.

Hazardous Polymerization: Will not occur by itself, but masses of more than one pound of product plus an aliphatic amine will cause irreversible polymerization with considerable heat.

Materials to Avoid: Bases, acids, amines and oxidizing materials.

11. TOXICOLOGICAL INFORMATION

Acute Toxicity

Product Information: Not established

Ingredient Information

Mineral oil: Orl-rat LD50 >5000 mg/kg, Skn-Rbt LD50 - 20,000 mg/kg

Hydrotreated neutral base oil: Orl-rat LD50 >5000 mg/kg, Skn-Rbt LD50 - 20,000 mg/kg

Acute Effects

Signs and Symptoms of Overexposure: Eye Irritation, Coughing, Sneezing

Inhalation: May cause coughing and sneezing.

Skin Contact: May be slightly irritating to sensitive users. Prolonged and repeated contact with skin without adequate cleaning may clog the pores of the skin and may result in disorders such as oil acne (folliculitis) in sensitive individuals.

Eye Contact: May cause stinging, tearing and redness.

Ingestion: May cause nausea, vomiting and diarrhea. Ingestion and subsequent vomiting may result in aspiration of the product into the lungs resulting in chemical pneumonitis, pneumonia and pulmonary edema.

Primary Route(s) of Exposure: Eyes, Inhalation

Primary Route(s) of Entry: Inhalation, Ingestion

Target Organs: Eyes, Lungs

Chronic Effects: None known

Carcinogenicity: Highly refined base oil blend (< 3 % DMSO extractable) ACGIH group A4; not classified as human carcinogen.

Medical Conditions Aggravated by Exposure: May aggravate existing eye and respiratory conditions such as asthma and dermatitis.

12. ECOLOGICAL INFORMATION

Product Data: Not established

Ingredient Data: Not established

Elimination Information: Expected to be not readily biodegradable. The major oil component is expected to biodegrade over period of 100-120 days in aerobic environment at temperature above 70°F (21°C), however finished product contains components that may persist in the environment. May contain components that bioaccumulate.

13. DISPOSAL CONSIDERATIONS

Product: Dispose of in accordance with local regulations. Smaller quantities can be disposed of with household waste.

Container: Empty remaining contents. Empty containers should be taken for local recycling, recovery or waste disposal. Empty containers may contain residues. Do not cut, weld or grind empty containers.

14. TRANSPORT INFORMATION

Road Transport

DOT Hazard Class: Non-Hazardous/ Non-Restricted

Sea Transport

IMDG/GGV See Class: Non-Hazardous/ Non-Restricted

Air Transport

ICAO/IATA Class: Non-Hazardous/ Non-Restricted

15. REGULATORY INFORMATION

U.S. Federal Regulations

Toxic Substances Control Act (TSCA): All components are included on the Inventory

Superfund Amendments and Reauthorization Act (SARA) Title III:

Immediate Hazard	Delayed Hazard	Fire Hazard	Pressure Hazard	Reactivity Hazard
Yes	No	No	No	No

New Zealand

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation.

HSNO Group Standard: Corrosion Inhibitors (Subsidiary Hazard) Group Standard 2017 - HSR002549

HSNO classification: 6.4A, 6.1E, 6.9B

NZIoC (New Zealand Inventory of Chemicals): All components are listed on the NZIoC inventory or are exempt.

Not classified as a Dangerous Good according to NZS5433:2007 Transport of Dangerous Goods on Land.

16. OTHER INFORMATION

Prepared by: Corrosion Technologies, Technical Services Department

Revision Date: 11 June 2020

Supersedes Date: 10 June 2019

Revision Indicator: v1.1 New Zealand SDS

National Fire Protection Association (704)

Health: 1 Flammability: 1 Reactivity: 0 Other:

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results and assume no liability for damage incurred by use of this material. All chemicals may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Final determination of suitability of the chemical and application of such products is the sole responsibility of the user. No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or any other nature are made hereunder with respect to the information contained herein or the chemical to which the information refers. It is the sole responsibility of the user to comply with all applicable Federal, State and Local Laws and Regulations. Any questions with regards to information contained herein should be referred to: U. S. Corrosion Technologies, LLC (972) 271-7361.